

DIE CAST ALUMINIUM FLOODLIGHT



OVERVIEW

 The **MAGIS MINI** LED Floodlight offers high reliability combined with superb photometric performance. The **MAGIS MINI**'s robust slim design ensures minimal build up of dirt and dust, making it the perfect floodlight for use in all industrial applications, including hazardous areas (Zone 2 & 21/22).

 APPLICATIONS

- Industrial lighting
- Outdoor lighting
- Security lighting
- Emergency lighting
- Dusty & dirty environments
- Zone 2, 21, 22



Made in
South Africa



L90B10
100 000 Hours



IP66
Rated



Rated up to
IK10



Surge Protection
Standard



SABS
Approved



Emergency Version
Available



MAGNITECH
LIGHTING INDUSTRIES

MAGNITECH - BENCHMARKING THE STANDARD
OF **QUALITY**



FEATURES & BENEFITS

STANDARDS:

SANS / IEC 60598-1
SANS / IEC 60079-15 (Zone 2)
SANS / IEC 60079-31 (Zone 21, 22)

LIGHT DISTRIBUTION:

Various light distributions available

LIGHT ENGINE:

High power 5050 LED's

TAMPER-PROOF FRAME:

2 lockable stainless steel clips

GASKET:

Silicon closed cell gasket ensures IP66 ingress protection

PROTECTOR:

High thermal shock resistant glass

SURGE PROTECTION

10kV/10kA - Standard
20kV/20kA - Optional

LED DRIVER

COMPARTMENT:

- Removable geartray
- EN approved driver
- High temperature terminal block
- SABS approved wiring

CABLE ENTRY:

20mm cable entry

MOUNTING BRACKET:


HDG floodlight mounting bracket. Stainless steel optional.

HOUSING:

AC44300 (LM6) Marine Grade Aluminium





DIMENSIONS



Description	Length	Width
MAGIS MINI (Flood Mounting)	454mm	234mm




Floodlight mounting




PHOTOMETRIC DATA


IES ROAD REPORT
PHOTOMETRIC FILENAME : MAGIS MINI T4 OPTICS.IES
POLAR GRAPH




Maximum Candela = 5414.313 Located At Horizontal Angle = 330, Vertical Angle = 45
#1 - Vertical Plane Through Horizontal Angles (0-180)
#2 - Vertical Plane Through Horizontal Angles (90-270)




IES ROAD REPORT
PHOTOMETRIC FILENAME : MAGIS MINI ME OPTICS.IES
POLAR GRAPH




Maximum Candela = 5941.734 Located At Horizontal Angle = 292.5, Vertical Angle = 55
#1 - Vertical Plane Through Horizontal Angles (0-180)
#2 - Vertical Plane Through Horizontal Angles (90-270)



IES ROAD REPORT
PHOTOMETRIC FILENAME : MAGIS MINI GENERAL FLOODLIGHT .IES
POLAR GRAPH



Maximum Candela = 4240.566 Located At Horizontal Angle = 360, Vertical Angle = 0
#1 - Vertical Plane Through Horizontal Angles (0-180)
#2 - Vertical Plane Through Horizontal Angles (90-270)



ORDERING DATA

	MAGIS MINI			
PRODUCT CODE	MLEDM020	MLEDM030	MLEDM040	MLEDM050
NOMINAL WATTAGE	20W	30W	40W	50W
NOMINAL FLUX (LM)	3845	5545	6925	8305
NOMINAL EFFICIENCY (LM/W)	192	181	174	166
LUMINAIRE LUMENS (LM)	3076	4436	5540	6644
LUMINAIRE EFFICIENCY RATIO (LER)*	154	145	139	133
COLOR TEMPERATURE	4000K (STANDARD) 2200K/3000K/5000K/6000K (OPTIONAL)			
LED LIFETIME (HOURS) @ TA 25 °C	L _{90B10} > 100 000 HRS			
CRI	>70			
DIFFUSER	Glass - IK08 (Standard) Polycarbonate - IK09/10 (Optional)			
NOMINAL INPUT VOLTAGE	220V-240V (STANDARD) 90V-305V (OPTIONAL)			
OPERATING TEMPERATURE	-20°C to 60°C			
SURGE PROTECTION	10kV (Standard) 20kV (Optional)			
IP RATING	IP66			
WEIGHT (BOX)	3.2KG			

* Values shown are AFTER both Thermal, Optical and Electrical losses.
Output will vary depending on optics utilised. Performance values are subject to ±5% variance

PRODUCT CODE LOGIC

MLED	-	F	XXX	-	X	X	X	-	X	X
Family Name			Wattage		CT	Optics	Mounting		Emergency	Zone Rating
			020 = 20W		2 = 2200K	0 = No Optics	2 = Trunion arm HDG		0 = Standard	0 = Standard
			030 = 30W		3 = 3000K	2 = ME	8 = Trunion arm 304 S/S		E = Emergency	2 = Zone 2
			040 = 40W		4 = 4000K	3 = FT	9 = Trunion arm 316 S/S			3 = Zone 21/22
			050 = 50W		5 = 5000K	5 = T4				
					6 = 6000K	6 = ME Wide				

Due to continuing R&D, the above data may change without prior notice. Please consult us for the latest available options. Warranties subject to our standard terms and conditions of sale. Visit our website for our full product range - www.magnitech.co.za.



MAGNITECH
LIGHTING INDUSTRIES (PTY) LTD



SABS
ISO 9001

21 RAEBOR ROAD BENROSE JOHANNESBURG 2094
P.O. BOX 27129 JEPPESTOWN 2043

T: +27 (0)11 618 2720 F: +27 (0)11 614 9603
E: SALES@MAGNITECH.CO.ZA
W: MAGNITECH.CO.ZA