



APPLICATION:

- → Street lighting
- → Highway lighting
- → Private road lighting
- → Parking lot lighting
- → Class A1, A2 and A3 roads



FEATURES & BENEFITS:

- → High efficiency
- → Lamp replacement without tools
- → Dust and moisture proof



LED OPTIONS

→ LED options available





LOCAL CONTENT

- → Local design
- → Local assembly





EYETINERA

HIGH PRESSURE DIE CAST ALUMINIUM STREETLIGHT WITH GLASS LENS



FEATURES

→ Body:

High pressure die cast aluminium

→ Diffuser:

Toughened glass lens

→ Reflectors:

One piece super pure aluminium

→ Locking Mechanism:

Stainless steel clip

→ Fixing:

Side or bottom entry

→ Control Gear:

SABS approved HPF

→ Rating:

IP66 rating

→ Gasket:

Silicon closed cell gaskets for durability and heat resistance

→ Gear tray:

Removable



APPLICATIONS

- → Street lighting
- → Highway lighting
- → Private road lighting
- → Parking lot lighting
- → Class A1, A2 and A3 roads



STANDARDS

- → SANS 475
- → SANS/IEC 60598





S/S clips:

Allows for tool-free lamp replacement



DIMENSION LINE DRAWINGS








EYETINERA 250 NAV-T.IES POLAR GRAPH

10586 7059 3529

Maximum Candela = 14117.64 Located At Horizontal Angle = 70, Vertical Angle = 62.5 # 1 - Vertical Plane Through Horizontal Angles (70 - 250) (Through Max. Cd.) # 2 - Horizontal Cone Through Vertical Angle (62.5) (Through Max. Cd.)

EYETINERA 250 NAV-T.IES ISOLUX LINES OF HORIZONTAL ILLUMINANCE



Distance In Units Of Mounting Height Values Based On 10 Meter Mounting Height 1/2 Maximum Candela Trace Shown As Dashed Curve (+) = Maximum Candela Point

The photometrics displayed above are one example of various lamps and light sources available for this fitting. Photometrics for other lamp variants are available on request.

ACCESSORIES

- 1. Photo Cell
- 2. MCB





ORDERING DATA

HID OPTIONS

DESCRIPTION	MV	FL	HPS	МН	XENON	CERAARC	WEIGHT
150W			Χ	X		X	12KG
250W	Χ		Χ	Χ			12KG
220W					Χ		12KG
360W					Χ		14KG
400W	Χ		Χ	Χ			14KG
600W			Χ				19KG

LED OPTIONS

LED options available

SUFFIX	OPTIONS & ACCESSORIES			
PC	PHOTO CELL			
PM	POLE MOUNT BRACKET			
МСВ	MINI CIRCUIT BREAKER			
WB	WALL BRACKET			
WP	WOODEN POLE BRACKET			

5 RAEBOR ROAD BENROSE JOHANNESBURG 2094

P.O. BOX 27129 JEPPESTOWN 2043

T: +27 (0)11 618 2720 F: +27 (0)11 614 9603 E: SALES@MAGNITECH.CO.ZA W: MAGNITECH.CO.ZA





