MAGFLEX



Industrial LED Rope Light



5W/m

460 lumens 8W/m

780 lumens



Industrial LED Rope Light



Hello Versatility!

The MAGFLEX is a rugged, high-performance industrial LED rope light engineered for demanding environments such as tunnels, conveyor belts, and enclosed mining corridors. Designed with safe extra-low voltage (SELV) operation, MAGFLEX delivers long continuous runs—up to 50 metres powered from a single end or 100 metres when powered from both ends.

This modular plug-and-play system is built for rapid deployment and durability, featuring a non-toxic silicone body, patented anti-dust coating, and optional glow-in-the-dark emergency indication. With flexible mounting, advanced power stabilisation, and class-leading energy efficiency, MAGFLEX is your go-to solution for reliable linear lighting in critical infrastructure environments.














- **Industrial Lighting**
- **Outdoor Lighting**
- Haulages
- Conveyors

- **Tunnel Lighting**
- Zone 1 (Available)








Configuration Examples




Single Channel (max)

Fed from one output




Double Channel (max)

Fed from two outputs



Dual Feed (max)

Fed from both ends





Technical Specifications



| FEATURE | LED ROPE SPECIFICATIONS | | | | |
|--------------------------------|--------------------------------------|--|--|--|--|
| NOMINAL POWER | 8W/m or 5W/m (Long range on request) | | | | |
| NOMINAL FLUX (LM) | 8W/m - 780lm 5W/m - 460lm | | | | |
| COLOR TEMPERATURE | 5700K (STANDARD) GREEN (OPTIONAL) | | | | |
| LED LIFETIME (HOURS) @ TA 25 ℃ | 54 000 HRS | | | | |
| CRI | >80 | | | | |
| DIFFUSER | SILICONE | | | | |
| VOLTAGE | 48VDC | | | | |
| OPERATING TEMPERATURE | -10°C to 40°C | | | | |
| IP RATING | IP67 | | | | |
| WEIGHT (BOX) | 2KG | | | | |
| BEAM ANGLE | 125° | | | | |
| INSTALLATION | SURFACE MOUNT | | | | |



| FEATURE | DRIVER BOX SPECIFICATIONS | | | |
|-----------------------|----------------------------------------------------|--|--|--|
| INPUT VOLTAGE | 90-305V ~ 50/60Hz | | | |
| IP RATING | IP66 | | | |
| MATERIAL | 306 STAINLESS STEEL (STANDARD) 316 SS (OPTIONAL) | | | |
| DIMENSIONS | 500mm X 400mm X 150mm | | | |
| WEIGHT | 17,7KG | | | |
| OPERATING TEMPERATURE | -10°C to 40°C | | | |



Ordering Data

| PRODUCT CODE | POWER | LUMENS | сст | CRI | REEL LENGTH | MAX COVERAGE |
|--------------|-------|------------------|-------|-----|-------------|--------------|
| FLX0208 | 8W/m | 780lm/m | 5700K | >80 | 25m | 100m |
| FLX0208G | 8W/m | Indication Light | Green | N/A | 25m | 100m |
| FLX0204 | 5W/m | 460lm/m | 5700K | >80 | 25m | 200m |

Due to continuing R&D, the above data may change without prior notice. Please consult us for the latest available options. Warranties subject to our standard terms and conditions of sale. Visit our website for our full product range - www.magnitech.co.za.

MAGNITECH - BENCHMARKING THE STANDARD OF QUALITY



MAGNITECH (PTY) LTD

21 RAEBOR ROAD, BENROSE, JOHANNESBURG, 2094 **TEL:** +27 11 618 2720 | **FAX:** +27 11 614 9603

EMAIL: SALES@MAGNITECH.CO.ZA

WWW.MAGNITECH.CO.ZA